

Airbus Contribution to the 3rd AIAA Ice Prediction Workshop

Alberto Della Noce

Airbus Operations SAS

Presented 23 September 2026

CC BY-NC-ND 4.0

This work is licensed by the author(s) under a **Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International licence (CC BY-NC-ND 4.0)**. To view a copy of this licence, visit <https://creativecommons.org/licenses/by-nc-nd/4.0/>.

Suggested citation: Della Noce, A. (2026). *Airbus Contribution to the 3rd AIAA Ice Prediction Workshop*. Presented at the 3rd AIAA Ice Prediction Workshop, online, 23 September 2026.



COMMERCIAL AIRCRAFT

3rd AIAA Ice Prediction Workshop

September 21st-24th, 2026


Alberto Della Noce
Flight Physics Capabilities
Airbus Operations SAS

AIRBUS

Outline

- ❖ Computational Framework
 - Overview & Solvers
- ❖ Numerical Parameters
- ❖ Test Cases & Convergence Studies
 - Aerodynamics
 - Particle Tracking
 - HTC & Freezing Fraction
 - Ice Shapes
- ❖ Conclusions

Computational Framework Overview



Computational Framework

Aerodynamic Solver: CODA


Jointly owned and developed by ONERA, DLR, and Airbus, CODA delivers highly accurate, flexible flow simulation for complex design and analysis.

Advanced Meshing & Discretisation: Generic unstructured elements. Finite Volume and Discontinuous Galerkin methods.

Robust Solvers & Optimization: Strong implicit solvers, Automatic Differentiation. Gradient-based optimization.

Physics Regimes & Integration: Compressible, incompressible flows. State-of-the-art turbulence models.

HPC Scalability & Performance: Hybrid parallelisation utilizing both multi-threading and MPI.



Computational Framework

Particle Tracking Solver: in-house tool


Developed in Airbus, it is an efficient polydisperse Lagrangian particle tracking solver designed to trace the motion of individual particles in fluid flows.

Implementation & Architecture: Utilizes libraries for high-performance ray tracing.

Physical Modelling & Trajectory: Spherical droplets. Supports rotating reference frames.

Physics Regimes & Integration: Polydisperse clouds, automatic adaptive cloud refinement, particle splashing and re-emission.

HPC Scalability & Performance: Cloud decomposition for parallelization and adaptive time stepping.



Lagrangian particle tracking on a CRM65 wing-body model. Credits: © Airbus / 2026

Computational Framework


Ice Accretion Solver: IGLOO3D

Developed by ONERA, IGLOO3D is a highly modular 3D numerical suite designed to predict and compute complex ice accretion on aircraft surfaces.

Core Thermodynamics Modules: Messinger mass and energy balance.

3D Ice Accretion Toolbox: Couples external aerodynamics and water droplet trajectory solvers with the internal thermodynamic module.

Simplified Roughness & Convective Transfer: Makkonen integral model, experimental correlations or Navier-Stokes-derived heat transfer coefficients.



IGLOO3D multistep ice accretion. Case 362 from the 1st AIAA Ice Prediction Workshop.
Credits: © Airbus / 2026

Numerical Parameters Used for IPW3 Simulations

CODA

- ❖ **Solver:** Finite Volume RANS smooth
- ❖ **Turbulence model:** negative Spalart-Allmaras
- ❖ **Convective fluxes:** 2nd order Roe scheme
- ❖ **Gradients:** extended Green-Gauss
- ❖ **Time integration:** implicit backward Euler
- ❖ **Linear solver:** matrix-free AD GMRES

PARTICLE TRACKING

- ❖ **Drag law:** Clift & Gauvin (sphere)
- ❖ **Cloud definition:** mono/poly dispersed (1-3-7-15 bins)
- ❖ **Cloud refinement:** automatic
- ❖ **Time integration:** Runge-Kutta 4th order
- ❖ **Splashing model:** No
- ❖ **Bouncing model:** No

IGLOO3D

- ❖ **Simulation type:** one step
- ❖ **Roughness height:** chord/1000
- ❖ **HTC:** Prandtl & Schlichting correlation (cf rough)
- ❖ **Thermodynamics:** Messinger
- ❖ **Ice density:**
 - 917 kg/m³ for glaze ice
 - Macklin formula for rime ice (750 kg/m³ < ρ < 917 kg/m³)
- ❖ **Node displacement:** algebraic


Test Cases

	NACA0012		ONERA M6
	AE3932	AE3933	
L4 - coarse	1 bin	1 bin	1 bin
	3 bins	3 bins	3 bins
	7 bins	7 bins	7 bins
	15 bins	15 bins	15 bins
L3 - medium	1 bin	1 bin	1 bin
	3 bins	3 bins	3 bins
	7 bins	7 bins	7 bins
	15 bins	15 bins	15 bins
L2 - fine	1 bin	1 bin	1 bin
	3 bins	3 bins	3 bins
	7 bins	7 bins	7 bins
	15 bins	15 bins	15 bins
L1 - extra fine	1 bin	1 bin	1 bin
	3 bins	3 bins	3 bins
	7 bins	7 bins	7 bins
	15 bins	15 bins	15 bins

❖ **ONERA M6 test cases were omitted** from the analysis due to a **lack of mesh convergence**.

❖ **Poor resolution of the trailing edge/wake region** had a significant effects on the calculation of aerodynamic coefficients.

❖ **No experimental data** available.



Mesh quality issues


❖ **Sharp trailing edge singularity:** highly skewed elements, collapsed faces at the junction.

❖ **Block interface transition:** significant jump in elements aspect ratio.



Solver issues

❖ **Turbulence model:** fails to accurately represent the shear layer.


❖ **Contour lines:** exhibit dependency on the mesh cell distribution.




Aerodynamics Convergence Study (1)



- ❖ **Good agreement** with respect to experimental data.
- ❖ **Mesh refinement** allows better capture of the stagnation point region.



Aerodynamics Convergence Study (2)




Input verification

- ❖ **Minor coefficient variations observed**, attributed to near-identical freestream conditions.

Mesh sensitivity

- ❖ **CL**: converged at **L3** mesh (< 0.02 lift counts difference vs. L1).
- ❖ **CD**: approaching convergence at **L2** mesh (~ 0.5 drag counts difference vs. L1).
- ❖ Further refinement (**ultra-fine**) required to fully assess **asymptotic drag behavior**.

Particle Tracking Convergence Study (1)



Input verification

- ❖ Negligible variation between cases AE3932 and AE3933 due to identical pressure distributions.



Droplet sensitivity

- ❖ **Monodisperse distribution underestimates** total water mass (~7%).
- ❖ **Impinged water mass plateau at 7 bins** (Langmuir distribution).

Mesh sensitivity


- ❖ **L3 mesh yields lower impinged mass than expected** compared to finer meshes. Investigation is ongoing.
- ❖ **L2 mesh provides a reasonable refinement** for accurate results.
- ❖ **L4 mesh demonstrates conservative** behavior.

Particle Tracking Convergence Study (2)



- ❖ Negligible variation between cases AE3932 and AE3933 due to nearly identical freestream conditions.
- ❖ **Monodisperse** simulations significantly **underestimate impingement limits**.
- ❖ **Mesh refinement** allows for **better peak capture**.

HTC Convergence Study





Input verification

- ❖ Negligible variation between cases AE3932 and AE3933, as the **3°C temperature difference** results in a **negligible impact on the local Reynolds number** used to compute the Nusselt number.

Mesh sensitivity



- ❖ **Significant sensitivity** observed at the **stagnation point**, with an approximately **38% difference** in HTC values between coarse and fine meshes.
- ❖ As the **HTC** model depends on the **curvilinear abscissa**, a **good discretization of the leading edge** region is required.

Freezing Fraction Convergence Study



- ❖ **Significant effect of temperature** on the two test cases.
- ❖ **Monodisperse** simulations predict a lower freezing fraction and a wider runback region.
- ❖ **Mesh refinement improved** predictions at the **stagnation point**.

Ice Shapes



- ❖ **Monodisperse** simulations significantly **underestimate** impingement limits.
- ❖ **Monodisperse** simulations predict **wider** runback.
- ❖ **Mesh refinement** allows for **better capture of peaks**.
- ❖ **Mesh refinement improves** the prediction of **ice thickness** at the **stagnation point**.
- ❖ In some cases, the **HTC model has limited accuracy**, leading to deviations from experiments.

Conclusions

Mesh

- ❖ A fine mesh (L2-like) is required to achieve aerodynamic mesh independence, ensuring accurate predictions of impinging water mass, HTC and ice shapes.
- ❖ Coarse meshes are conservative regarding collection efficiency.
- ❖ Further investigation of the L3 mesh is required, as it may affect the CFD and particle tracking solution.

Droplet distribution

- ❖ Monodisperse simulations underestimate impinging water mass.
- ❖ Monodisperse simulations predict lower freezing fractions and wider runback regions but underpredict impingement limits.
- ❖ Langmuir distributions effectively represent impinging water mass convergence in Appendix C conditions and should be used for further analysis.

Modeling

- ❖ The used HTC model (Prandtl & Schlichting correlation) may lack accuracy for complex glaze ice configurations.

Thank you

© Copyright Airbus 2026 / 3rd AIAA Ice Prediction Workshop - 21-24th September 2026

This document and all information contained herein is the sole property of Airbus. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. This document shall not be reproduced or disclosed to a third party without the expressed written consent of Airbus. This document and its content shall not be used for any purpose other than that for which it is supplied. Airbus, its logo and product names are registered trademarks.